

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use: Alcohol resistant foam. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

UNUSUAL FIRE & EXPLOSION HAZARDS

May travel considerable distance to source of ignition and flash back.

6. ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush area with water.

7. HANDLING & STORAGE**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place.

STORAGE CLASS

Flammable liquid storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std	8h TWA		STEL	
METHANOL	WEL (skin)	200 ppm	260 mg/m ³	250 ppm	310 mg/m ³
ETHANOL	WEL	1000 ppm	1900 mg/m ³		

WEL – Workplace Exposure Limit; 8h TWA – 8-hour Time-Weighted Average; STEL – Short-Term EL.

PROTECTIVE EQUIPMENT**ENGINEERING MEASURES**

Well-ventilated area. Provide explosion proof ventilation for high concentrations.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Colourless Liquid
ODOUR	Odour of alcohol
SOLUBILITY	Soluble in water.
BOILING POINT	~ 78°C 760 mmHg
RELATIVE DENSITY	~ 0.8 @ 20°C
FLASH POINT	~ 13°C

10. STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

11. TOXICOLOGICAL INFORMATION**INHALATION**

Solvent vapours are hazardous and may cause nausea, sickness and headaches.
Central nervous system depression.

INGESTION

May cause discomfort if swallowed. May cause stomach pain or vomiting.
Drowsiness, dizziness, disorientation, vertigo.

SKIN CONTACT

Prolonged or repeated contact leads to drying of skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

The product is not expected to be hazardous to the environment.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

Material Safety Data Sheet
SHEPARD'S FIXATIVE/DILUENT
(80% ALCOHOL)

14. TRANSPORT INFORMATION

**IMDG**

UN# 1170
 Class 3
 PG II
 Proper shipping name: Ethanol Solution
 Marine Pollutant: No

RID / ADR

UN# 1170
 Class 3
 PG II
 Proper shipping name: Ethanol Solution

IATA

UN# 1170
 Class 3
 PG II
 Proper shipping name: Ethanol Solution

15. REGULATORY INFORMATION

LABELLING

Highly Flammable



Harmful

RISK PHRASES

R11 Highly flammable
 R20/21/22 Harmful by inhalation, in contact with skin and if swallowed
 R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed

SAFETY PHRASES

S1/2 Keep locked up and out of the reach of children
 S7 Keep container tightly closed
 S16 Keep away from sources of ignition - No smoking
 S36/37 Wear suitable protective clothing and gloves
 S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

CHIP for everyone HSG(108). Workplace Exposure Limits EH40.

16. OTHER INFORMATION**GENERAL INFORMATION**

This safety data sheet covers all codes for this product.

REVISION COMMENTS

Methanol limits adjusted.

8h TWA (Time-Weighted Average) replaces Long-Term Exposure Limit (LTEL)

REVISION DATE

06-2009

REV. NO./REPL. SDS GENERATED

4 / 06-2008

RISK PHRASES IN FULL

R11	Highly flammable
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R68/20/21/22	Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed