

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

PRODUCT NAME WEIGERT'S STAIN 1

PRODUCT CODE 64049x

SUPPLIER Clin-Tech Limited  
Unit G, Perram Works  
Merrow Lane  
Guildford, Surrey  
GU4 7BN  
UK

Telephone +44 (0)1483 301902  
Fax +44 (0)1483 301907  
Email info@clin-tech.co.uk  
Website www.clin-tech.co.uk

## 2. HAZARDS IDENTIFICATION

### CLASSIFICATION ACCORDING TO REGULATION (EC) No 1272/2008 [EU-GHS/CLP]

Flammable liquids (Category 2) H225  
Acute toxicity, Oral (Category 4) H302  
Specific target organ toxicity - single exposure (Category 2) H371

### LABELLING ACCORDING TO REGULATION (EC) No 1272/2008 [EU-GHS/CLP]

DANGER



### Hazard statement(s)

H225 Highly Flammable liquid and vapour  
H302 Harmful if swallowed  
H371 May cause damage to organs

### Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces — No smoking  
P260 Do not breathe mist/vapours/spray

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Name	EC #	CAS #	Content	Classification
ETHANOL C <sub>2</sub> H <sub>5</sub> OH	200-578-6	64-17-5	60-100%	Flam. Liq. 2 H225
METHANOL CH <sub>3</sub> OH	200-659-6	67-56-1	3-10%	Flam. Liq. 2; Acute Tox. 3; STOT SE 1 H225 H301 H311 H331 H370
HAEMA- TOXYLIN [CI 75920]	208-237-3	517-28-2	1%	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3 H302 H315 H319 H335
7,11b-dihydroindeno[2,1-c]chromene-3,4,6a,9,10(6H)-pentol				

## 4. FIRST-AID MEASURES

### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

### INGESTION

Do not induce vomiting. Never make an unconscious person vomit or drink fluids. Get medical attention immediately. Show the label or this document to the physician.

### SKIN CONTACT

Remove contaminated clothes and rinse skin thoroughly with water. If symptoms occur seek medical attention.

### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eyelids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

---

## 5. FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Use: Dry chemical, Alcohol-resistant foam, Water spray, or Carbon dioxide.

### UNUSUAL FIRE AND EXPLOSION HAZARDS

May travel considerable distance to source of ignition and flash back. May form explosive or toxic mixtures with air. Vapour explosion and poison hazard indoors, outdoors and in sewers. Forms harmful carbon oxides on combustion.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this SDS. Evacuate personnel from the affected area. Extinguish all ignition sources. Avoid sparks, flames, heat. Ventilate area.

### ENVIRONMENTAL PRECAUTIONS

Do not allow spillage to enter watercourses, drains or sewers. Fire Brigade and Local authority must be informed if this happens as a potential explosive hazard may be created. Stop leak if possible without risk.

### SPILL CLEAN-UP METHODS

Provide ventilation and confine spill. Do not allow runoff to sewer. Inform Authorities if large amounts are involved. Absorb with vermiculite, dry sand or earth – do NOT use sawdust or other combustible materials. Shovel up residue and collect for authorised disposal (see section 13). Flush area with plenty of water.

## 7. HANDLING & STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

### STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a cool, dry well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. May attack some plastics, rubber and coatings.

### STORAGE CLASS

Flammable liquid storage.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std	8h TWA		STEL	
ETHANOL	WEL	1000 ppm	1920 mg/m <sup>3</sup>		
METHANOL	WEL (skin)	200 ppm	260 mg/m <sup>3</sup>	250 ppm	333 mg/m <sup>3</sup>

*WEL – Workplace Exposure Limit; 8h TWA – 8-hour Time-Weighted Average; STEL – Short-Term EL.*

### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. Provide explosion-proof ventilation for high concentrations.

### PROTECTIVE EQUIPMENT



### HAND PROTECTION

Use protective gloves made of: Butyl rubber (immersion protection) or Nitrile rubber (splash protection). The most suitable glove should be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

### EYE PROTECTION

Wear approved, tight-fitting safety glasses where splashing is probable.

### RESPIRATORY EQUIPMENT

Self-contained breathing apparatus where high vapour levels are likely.

### OTHER PROTECTION

Provide eyewash station.

## HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Brown Liquid
ODOUR	Pungent (alcohol)
(SOLUBILITY) / MISCIBLE WITH:	Water; Ethanol; Ether; Benzene; Organic solvents
MELTING POINT	~ -114 °C
BOILING POINT	~ 78 °C
FLASH POINT (CLOSED CUP)	~ 13 °C
AUTO-IGNITION TEMP	~ 790 °C
SPECIFIC GRAVITY	0.79 @ 20 °C
VAPOUR PRESSURE	58.1 hPa @ 20 °C
EXPLOSION LIMIT – UPPER	19 %
EXPLOSION LIMIT – LOWER	3.3 %

---

## 10. STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Extremes of temperature, direct sunlight.

### INCOMPATIBLE MATERIALS

Strong oxidizers, Acids, Reducing agents, Alkali metals.

Can react vigorously with chloroform in the presence of sodium and sodium hydroxide.

### HAZARDOUS DECOMPOSITION PRODUCTS

During fire, toxic gases (CO, CO<sub>2</sub>) are formed.

---

## 11. TOXICOLOGICAL INFORMATION

### INHALATION

May be harmful by inhalation. May cause respiratory tract irritation.

### INGESTION

Harmful if swallowed.

### SKIN CONTACT

May be harmful if absorbed through the skin. May cause skin irritation.

### EYE CONTACT

Causes serious eye irritation.

## SIGNS AND SYMPTOMS OF EXPOSURE

Central nervous system depression, narcosis, nausea, dizziness, damage to the heart.,  
gastrointestinal disturbance, may cause convulsions.

---

## 12. ECOLOGICAL INFORMATION

### ECOTOXICITY

Not regarded as dangerous for the environment. However, the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

---

## 13. DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Incinerate in suitable combustion chamber. Dispose of waste and residues in accordance with local authority requirements.

---

## 14. TRANSPORT INFORMATION

	UN #	Class	Packing	Proper shipping name
<u>RID / ADR</u>	1170	3	II	Ethanol Solution
<u>IATA</u>	1170	3	II	Ethanol Solution
<u>IMDG</u>	1170	3	II	Ethanol Solution

### SIGNAGE



### ENVIRONMENTAL HAZARDS

RID / ADR	No
IATA	No
IMDG	No

---

## 15. REGULATORY INFORMATION

### STATUTORY INSTRUMENTS

This MSDS complies with regulation (EC) no. 1907/2006.  
Workplace Exposure Limits EH40/2011.

---

## 16. OTHER INFORMATION

### GENERAL INFORMATION

This safety data sheet covers all codes for this product.

### REVISION INFORMATION

Revision No.	05
Revision Date	09/2015
Comments	CHIP regulations removed
Replaces Document Generated	02/2013

## HAZARD STATEMENTS IN FULL

H225	Highly Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs
H371	May cause damage to organs