

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

PRODUCT NAME KINYOUN'S CARBOL FUCHSIN

PRODUCT CODE 62060x

<u>SUPPLIER</u>	Clin-Tech Limited	Telephone	+44 (0)1483 301902
	Unit G, Perram Works	Fax	+44 (0)1483 301907
	Merrow Lane		
	Guildford, Surrey	Email	info@clin-tech.co.uk
	GU4 7BN	Website	www.clin-tech.co.uk
	UK		

2. HAZARDS IDENTIFICATION

CLASSIFICATION ACCORDING TO REGULATION (EC) No 1272/2008 [EU-GHS/CLP]

Flammable liquids (Category 3)	H226
Acute toxicity, Inhalation (Category 4)	H332
Acute toxicity, Oral (Category 4)	H302
Skin Corrosion (Category 1B)	H314
Germ Cell Mutagenicity (Category 2)	H341
Carcinogenicity (Category 2)	H351

LABELLING ACCORDING TO REGULATION (EC) No 1272/2008 [EU-GHS/CLP]

DANGER



Hazard statement(s)

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer

Precautionary statement(s)

P261	Avoid breathing fumes/mist/vapours
P280	Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310	Immediately call a POISON CENTER or doctor/physician

3. COMPOSITION / INFORMATION ON INGREDIENTS

Name	EC #	CAS #	Content	Classification
PHENOL	203-632-7	108-95-2	3-10%	Muta 2, Acute Tox. 3, STOT RE 2, Skin Corr. 1B H301 H311 H314 H331 H341 H373
BASIC FUCHSIN [CI 42510]	211-189-6	58969-01-0	1-5%	Acute Tox. 4, Resp. Sens. 1, Skin Sens. 1, Carc. 2 H302 H317 H334 H351
4-[(4-Aminophenyl)-(4-imino-1-cyclohexa-2,5-dienylidene)methyl] aniline hydrochloride				
ETHANOL	200-578-6	64-17-5	10-25%	Flam. Liq. 2 H225
METHANOL	200-659-6	67-56-1	<1%	Flam. Liq. 2; Acute Tox. 3; STOT SE 1 H225 H301 H311 H331 H370

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Get prompt medical attention.

INGESTION

Do not induce vomiting. Rinse mouth with water. Never make an unconscious person vomit or drink fluids. Get medical attention immediately.

SKIN CONTACT

Remove contaminated clothes and rinse skin thoroughly with water. Seek medical attention.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eyelids. Continue to rinse for at least 15 minutes. Get medical attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Alcohol-resistant foam. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

UNUSUAL FIRE AND EXPLOSION HAZARDS

May travel considerable distance to source of ignition and flash back. May form explosive or toxic mixtures with air. Vapour explosion and poison hazard indoors, outdoors and in sewers. Forms harmful carbon oxides on combustion.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid breathing fumes. Ensure adequate ventilation. Evacuate personnel.

ENVIRONMENTAL PRECAUTIONS

Do not allow spillage to enter watercourses, drains or sewers. Stop further spillage if possible without risk.

SPILL CLEAN-UP METHODS

Absorb with sand or vermiculite, and sweep up into bag and hold for hazardous disposal. Avoid creating dust. Ventilate area.

7. HANDLING & STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide adequate exhaust where vapour or mist is raised.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place.

STORAGE CLASS

Chemical storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std	8h TWA		STEL	
PHENOL	WEL (skin)	5 ppm	19 mg/m ³	10 ppm	38 mg/m ³
ETHANOL	WEL	1000 ppm	1920 mg/m ³		
METHANOL	WEL (skin)	200 ppm	260 mg/m ³	250 ppm	333 mg/m ³

WEL – Workplace Exposure Limit; 8h TWA – 8-hour Time-Weighted Average; STEL – Short-Term EL.

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

PROTECTIVE EQUIPMENT



HAND PROTECTION

Use protective gloves. The most suitable glove should be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved, tight-fitting safety glasses where splashing is probable.

RESPIRATORY EQUIPMENT

Self-contained breathing apparatus where high vapour levels are likely.

OTHER PROTECTION

Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Dark Purple Liquid
ODOUR	Phenolic / alcoholic
SOLUBILITY / MISCIBLE WITH	Water, Ethanol
FLASH POINT	~ 40 °C

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

INCOMPATIBLE MATERIALS

Bases, Amines, Alkali metals, Metals, Permanganates

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

(PHENOL) IARC: 3 – Group 3 – Not classifiable as to its Carcinogenicity to Humans

INHALATION

Harmful if inhaled. Causes respiratory tract irritation.

INGESTION

Harmful by ingestion.

SKIN CONTACT

Harmful by skin absorption. Causes severe skin burns.

EYE CONTACT

Causes severe eye damage.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment. However, the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

	UN #	Class	Packing	Proper shipping name
<u>RID / ADR</u>	2924	3 (8)	III	Flammable liquid, corrosive, n.o.s. (Ethanol, Phenol)
<u>IATA</u>	2924	3 (8)	III	
<u>IMDG</u>	2924	3 (8)	III	

SIGNAGE



ENVIRONMENTAL HAZARDS

RID / ADR	No
IATA	No
IMDG	No

15. REGULATORY INFORMATION

STATUTORY INSTRUMENTS

This MSDS complies with regulation (EC) no. 1907/2006.
Workplace Exposure Limits EH40/2011.

16. OTHER INFORMATION

GENERAL INFORMATION

This safety data sheet covers all codes for this product.

REVISION INFORMATION

Revision No.	06
Revision Date	09/2015
Comments	CHIP regulations removed
Replaces Document Generated	05/2013

HAZARD STATEMENTS IN FULL

H225	Highly Flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H370	Causes damage to organs
H373	Causes damage to organs through prolonged or repeated exposure